

PATENT APPLICATION SERIAL NO. 08/485113

U.S. DEPARTMENT OF COMMERCE  
PATENT AND TRADEMARK OFFICE  
FEE RECORD SHEET

6646-108N4

240 AH 07/13/95 08485113  
1 101 730.00 CK 6646-108N4



08/485113

APPLICATION

OF

RONALD A. KATZ

FOR

UNITED STATES LETTERS PATENT

ON

MULTIPLE FORMAT TELEPHONIC

INTERFACE CONTROL SYSTEM

DOCKET No. 4646-108C

NO. OF DRAWINGS Five (5)

ATTORNEYS  
NILSSON, ROBBINS, DALGARN,  
BERLINER, CARSON & WURST  
LOS ANGELES, CALIFORNIA

485, 113

MULTIPLE FORMAT TELEPHONIC  
INTERFACE CONTROL SYSTEM

Abstract of the Disclosure

5           Call data signals actuated by a telephone  
terminal are provided from a telephone communication  
system to indicate call data as the called number, the  
calling number and the calling equipment. The call data  
signals address related control functions for selec-  
10           tively interfacing a live operator terminal or a  
multiple format multiple port data processing system.  
The interface connection involves providing a specific  
format as for automated processing or to prompt an  
operator. Screening tests and format selection are  
15           performed to make a determination. Individual telephone  
terminals and individual data formats are arranged and  
interfaced under controlled conditions specified by the  
call data. Time tests, history tests and demographic  
tests may be executed in addition to basic selection and  
20           qualification tests. Control may be executed from  
active data storage for assembled control words and  
record words. Record words for individual calls may be  
stored along with developed data.



08/485113

1

MULTIPLE FORMAT TELEPHONIC  
INTERFACE CONTROL SYSTEM

Related Subject Matter

5 This is a continuation-in-part of Application  
Serial No. 260,104<sup>A, B,</sup> filed October 20, 1988 and entitled  
"Telephonic Interface Control System"<sup>now U.S. Pat. No. 4,930,150,</sup> which is a  
continuation-in-part of Application Serial No. 018,244  
10 filed February 24, 1987 and entitled "Statistical  
Analysis System For Use With Public Communication  
Facility", now United States Patent No. 4,792,968, which  
was a continuation-in-part of Application Serial No.  
753,299 filed July 10, 1985 and entitled "Statistical  
15 Analysis System For Use With Public Communication  
Facility", now abandoned.

Background and Summary of the Invention  
<sup>A</sup>  
<sup>Ins</sup>  
<sup>B2</sup>

Over the past several years, substantial  
expansion has occurred in the technology of combining  
20 telephonic and computer systems. For example, tele-  
phone systems have been developed to readily transmit  
digital data. Various forms of modems are in wide-  
spread use to intercouple telephones and computers.  
However, at a more personal level, it also has been  
25 proposed to utilize the traditional dialing buttons of  
telephone instruments to provide digital data, as for  
various processing. In accordance with such arrange-

56/097-ETP-58483

2

ments, voice messages prompt callers to provide data by actuating the alphanumeric buttons of conventional telephones. These systems have been proposed in association with computers to provide various services and one such system is disclosed in United States Patent No. 4,792,968, issued December 20, 1988, to Ronald A. Katz from an Application Serial No. 018,244 filed February 24, 1987.

With respect to telephonic-computer systems, attaining the interface format desired by an individual caller is sometimes complex and burdensome. Specifically, callers may be misdirected, screening may be ineffective and delays may be cumbersome. Also, records may be poor or non-existent. Furthermore, some situations exist where interface to a live operator is an important alternative. As a consequence, a need exists for an improved interface system for selectively interfacing a considerable number of individual callers with a multiple format processor, as to attain efficient and economical digital and vocal exchanges along with prompting and data accumulation.

In general, the present invention comprises a telephonic-computer interface system accommodating digital and vocal (analog) telephonic communication and capable of handling a large number of calls to selectively interface prompted live-operator stations or formats in a computer processor. The selected interface is controlled, as by call (called number, calling number, etc.) and can be altered under control of an operator, developed data or operating conditions. Accordingly, the system of the present invention interfaces: (1) a telephonic communication facility including remote terminals for individual callers, e.g. conventional telephone instruments including voice communication means, and digital input means in the

944990-060795

form of alphanumeric buttons for providing data and  
 (2) either a prompted live-operator station or a  
 multiple port, multiple format data processor for con-  
 currently processing data from a substantial number of  
 callers with respect to any of several formats.

The interface system incorporates a con-  
 troller for receiving calls from remote terminals for  
 association with ports in the telephonic computer  
 apparatus, and which receives signal-represented call  
 data (representing "calling" and "called" telephone  
 numbers) along with equipment information. An index  
 apparatus is controlled, as by the signal-represented  
 call data, to select initially a live-operator or  
 machine format of the processor so as to specify any  
 conditions for the interface, at least one of the  
 formats including at least one condition. A test  
 apparatus may determine whether or not an individual  
 call attains specified conditions and thereby controls  
 switching structure for providing the actual interface.  
 If a live-operator terminal is selected, or indicated as  
 a secondary format, prompt data is provided to a select  
 station. Data is recorded and processing procedures  
 also may be controlled by call data.

#### Brief Description of the Drawings

In the drawings, which constitute a part of  
 this specification, an exemplary embodiment exhibiting  
 various objectives and features hereof is set forth,  
 specifically:

FIGURE 1 is a block diagram of a system con-  
 structed in accordance with the present invention;

FIGURE 2 is a flow diagram illustrating the  
 operating process of the system of FIGURE 1;

FIGURE 3 is a block diagram of a component  
 portion of the system of FIGURE 1;

562990-CT58488

4

FIGURE 4 is a diagrammatic representation of a binary control word as registered and utilized in the system of FIGURE 1;

5      FIGURE 5 is a diagrammatic representation of a binary data record word as utilized and recorded in the system of FIGURE 1; and

FIGURE 6 is a flow diagram illustrating the operating process of the structure represented in FIGURE 5.

10

#### Description of the Illustrative Embodiment

As required, a detailed illustrative embodiment of the present invention is disclosed herein. However, physical communication systems, data formats, and operating structures in accordance with the present invention may be embodied in a wide variety of forms, some of which may be quite different from those of the disclosed embodiment. Consequently, the specific structural and functional details disclosed herein are merely representative; yet in that regard, they are deemed to afford the best embodiment for purposes of disclosure and to provide a basis for the claims herein which define the scope of the present invention.

Referring initially to FIGURE 1, a series of remote terminals T1-Tn (telephone instruments) are represented (left). The terminals T1-Tn are generally similar and accordingly only the terminal T1 is shown in any detail. The indicated terminals T1-Tn represent the multitude of telephone terminals existing in association with a communication facility CO which may comprise a comprehensive public telephone network.

The communication facility CO, along with the individual terminals T1-Tn, is coupled to a central processing station CS generally indicated by a dashed-line block. Generally with regard to the station CS,

35

individual terminals T1-Tn are interfaced either with a processor P (upper right) or one of several live-operator stations OS1-OSn (lower left) through a call receiver unit CU and a switch SW. Essentially, the processor P and the switch SW cooperate (line 9) to control interfaces, with the processor P providing interface formats either (or both) to automate an interface or prompt a live operator at a station OS1-OSn. Note that the interface formats are stored as described below in the processor P.

In accordance herewith, individual telephone calls are preliminarily processed on the basis of signal-represented call data to identify a specific operating format for a station or the processor P. The preliminary processing may invoke screening tests to impose conditions or establish a test criteria for the switch SW to determine the acceptability of the call to interface with a specific operating format.

Calls are selectively processed according to a specific operating format as indicated by call data. At any instant of time, the collective interface may involve several thousand calls simultaneously being processed through ports of the processor P. Exemplary selected formats of the processor might include: public polls, lotteries, auctions, promotions, sales operations and games. Accordingly, the stations OS1-OSn may comprise a substantial number and the processor P may take the form of a sizable computer capable of simultaneously processing many calls involving several different formats. Although numerous possible configurations are available, for purposes of explanation, the processor P is illustrated simply as a block with multiple ports. Note that while the switch SW and the processor P may be integrated in a single system, they

662090-1154180



are separately illustrated to isolate the detailed structure and process of the present invention.

Input lines LI1 through LI<sub>n</sub> from the call receiver unit CU enter the switch SW to provide calling data and communication paths. Output lines LO1 through LO<sub>n</sub> function between the switch SW and the processor P as lines LS1-LS<sub>n</sub> operate to serve the stations OS1-OS<sub>n</sub>. Note that various multiplexing techniques are well known in the telephonic art to communicate call data and may be employed in the system.

Considering the system somewhat summarily, individual calls originating at the terminals T1-T<sub>n</sub> are coupled through the communication facility CO and the call receiver unit CU to the switch SW. Call data, representative of calls, actuates the switch SW to preliminarily process each call based on the desired format. For example, depending on the desired format (indicated by the called number and/or the equipment data signals) calls are selectively coupled and processed. Furthermore, record data is assembled for storage.

Considering the system of FIGURE 1 in somewhat greater detail, the exemplary telephone terminal T1 includes a handpiece 10 (microphone and earphone) and a panel 12 provided with a rectangular array of push buttons 14 in a conventional configuration. Of course, the handpiece 10 accommodates analog signals while the panel 12 is a digital apparatus. Generally, the handpiece 10 serves to manifest analog or voice signals to a caller.

In accordance with conventional telephone structure, alphabetic and numeric designations are provided on the buttons 14. For example, several of the buttons 14 carry three letters along with a decimal digit. Specifically, the button designated with the numeral "2" also carries the letters "A", "B" and "C".

004511 060735  
564090 E 1158480

Thus, the buttons 14 encompass the numerals "0-9" two symbols, and the alphabet except for the letters "Q" and "Z". Consequently, the buttons 14 substantially accommodate the entry of decimal and alphabetic data.

5           At this stage, some specific aspects of the communication facility CO are noteworthy. Essentially, with telephonic dialing, the communication facility CO couples selective terminals (from the multitude of terminals T1-Tn) to the call receiver unit CU. In that  
10       regard, the unit CU at the central station CS may be reached by any of a plurality of called numbers. For example, the call unit CU might be reached by any of twenty telephone dialing numbers, each associated with a specific operating format of the processor P. One  
15       called number or set of numbers might be associated with an auction format of the processor P. Another number or set of numbers might be associated with sales operating formats. Still another called number or set of numbers might identify a game format, and so on.

20           Incoming calls to the call receiver unit CU are identified by call data in accordance with telephone system techniques. As described below, the call data may specifically include digital signals representative of the called number (DNIS), the calling number  
25       (ANI) (terminal number), and the terminal equipment.

          In addition to attaining a preliminary interface with a selected format, individual calls may be screened based on the called number (identifying an operating format) and the calling number (caller identification) or the equipment. That is, the system of  
30       the present invention is based on a realization that signal-represented call data can be effectively utilized to selectively interface individual callers at remote terminals with specific operating formats of a data  
35       processor.

8

Considering the call data in somewhat greater detail, in accordance with current telephone systems, the communication facility CO may provide signal-represented call data for: the "called" number, the  
 5 "calling" number, and the equipment involved, e.g. "pulse" or "tone" terminal. Specifically, operating telephone equipment termed "DNIS" automatically provides the called telephone number in digital form from the communication facility CO. Somewhat similarly, existing  
 10 telephonic equipment designated "ANI" automatically indicates the caller's (calling) number in digital signal represented form. Generally, time shared lines carry such call data and also may provide call data indicating equipment. Thus, the call unit CU may  
 15 receive the called number, the calling number, and a calling equipment designation (pulse or tone), collectively termed call data, which data is utilized to establish control functions, as for example to select an operating format for a station OS1-OSn or the processor  
 20 P.

As described in detail below, call data is registered in the switch SW to perform distinct control operations. Specifically, a selection section 16 of the switch SW identifies a specific desired format for the  
 25 stations OS1-OSn or the processor P. Depending on the format, a testing section 18 of the switch SW may screen calls for interface connections.

Recognizing that the possibilities are great, formats for calls in accordance with the disclosed  
 30 embodiment may be of three different classes. Specifically, call formats may specify any of the following operations:

1. couple to live operator station if  
 35 possible or in accordance with a predeter-

mined criteria; if no operator station available, couple to processor;

2. interface to processor;

3. either above format, but selectively re-couple to live operator station or processor depending on secondary conditions.

The ramifications of individual formats within the above classes may vary considerably; however, some examples will illustrate possibilities. A marketing format (class 1) might interface callers to a live operator if an operator is available. Upon receiving a call, the operator station OS1-OSn (FIGURE 1) also receives and displays prompting format data for the attending operator. If an operator is not available (all stations OS1-OSn busy) the system provides an interface with the processor P and a format as to record the data for a return call by an operator. Alternatively, the processor completes the transaction with data provided by the caller that may be digital, digital and voice, or voice.

In a game format, say of class 2, a caller may be limited to interface the processor P. the interface may be contingent on initial test conditions, e.g. call data, caller record, time, etc.

Formats of class 3 involve a switch between live operator and processor depending on secondary conditions. For example, a polling format may switch from the processor P to an operator station OS1-OSn if the caller fails to provide digital data in a responsive form. Alternatively, an operator may command a switch to the processor P upon identifying a specific caller from whom data is to be taken.

In the illustrative system of FIGURE 1, an operating process is executed as illustrated in FIGURE

1062090-ET-52800

2. Each incoming call prompts a preliminary query as indicated by a block 20 concerning the availability of a line or port. In the absence of an available line, a busy signal is provided as indicated by the block 22. Alternatively, an available line results in a preliminary interconnect as indicated by a block 24 setting a conditional connection into operation.

As indicated by a block 26, during the screening or testing interval (typically measured in seconds or fractions of seconds) the caller remains on line and may receive a message. That is, the caller might hear silence or may continue to hear the traditional telephonic ringing sound. Alternatively, the caller might be given a brief vocal message to "stand by" as indicated by the block 26. In any event, the caller is held "on line" while the process continues.

With a call on a line, the communication facility CO (FIGURE 1) provides signal-represented call data, e.g. the called number, the calling number, and the equipment designation. As indicated by block 28 (FIGURE 2) signals representative of the call data are captured to perform preliminary control and processing operations as will now be considered. Note that the selected formats will fall within one of the classes as stated above.

The initial test is illustrated by a query block 25 representing an operation to distinguish calls of class 1 (operator) and class 2 (processor). Calls for a format seeking an operator prompt a "yes" response from the block 25 and proceed to the test of a block 27, "is an operator available?" A "yes" determination advances the process to an operation indicated by a block 29. Specifically, the block 29 represents the operations of coupling a caller to an operator station and transferring the appropriate format data to the

564997 E F F 53420

station for prompting the operator. If no operator is available (block 27) the process proceeds with automated control to attain an interface in accordance with an appropriate format. Specifically, a control word is  
 5 fetched (block 36) to establish an operating format for interfacing the call. In that regard, the specified format may be very simple. For example, the call simply may be prompted to indicate identification for a return call. Alternatively, the format may incorporate condi-  
 10 tions or other complications as explained below.

Returning to the query block 25, if the call is to be coupled to the processor, an initial test operation is indicated by a block 30. A validity test is performed, for example, a list of calling numbers may  
 15 be compiled that are to be denied access to any interface with the processor P. Negative calling numbers may result either by the choice of the person responsible for the calling number terminal, or by the choice of the service operating the processor P (FIGURE 1). For  
 20 example, an accumulation of prior improper transactions from a terminal designated by a specific telephone number may provide a basis for complete disqualification. Equipment also may disqualify.

Recognizing that various circumstances may be  
 25 involved with respect to the total disqualification of a calling terminal, in accordance herewith the test involves formulation of a validity bit as indicated by the query block 30. Acceptable calls set the validity bit at a binary "1".

30 If the calling terminal is invalid, ("no" from the block 30) the call is rejected as indicated by the block 32 with or without a message and the line is released as indicated by the block 34. Note that the time interval involved is very short and the rejection

0049513-060795  
 562090-CT58430

message may take various forms including a verbal comment, a busy signal or simply a disconnected signal.

If a positive validity bit ("1") is formed at the junction of the query block 30, a control word is  
 5 fetched under command of the called number as indicated by the block 36. As described in detail below, a control word is available for each operating format of the processor P and is utilized to impose the conditions for an interface and the terms of any associated  
 10 billing.

As indicated in FIGURE 2, the fetched control word of the block 36 prompts an inquiry as to the conditions attendant the selected operating format as indicated by a query block 38. That is, in the process, the  
 15 query of block 38 determines whether further conditions are imposed for attaining interface with the processor P. If no further conditions are imposed, the format is initiated by pursuing the connected interface as indicated by a block 40. Also, as indicated by a block 42,  
 20 the call is logged or recorded as with respect to billing data for example.

If access to a format involves conditions ("yes" from the query block 38), tests are specified as illustrated by a block 44. That is, conditions for the  
 25 interface are specified by the block 44. Of course, the specific tests may involve various criteria; however, in the illustrative embodiment, the conditions involve time, history and demographics. Each exemplary condition will now be considered somewhat preliminarily.

In the disclosed embodiment, time tests  
 30 involve testing the time of the call against certain limitations. For example, it may be desirable to limit some formats to specific time intervals as in relation to a television broadcast, a real time auction and so  
 35 on. Note that the time tests also may be related to

004434-0000

specific terminal control and geographic areas treated on the basis of telephone area codes. Specific examples will illustrate.

5 Assume an operating game format that propounds questions to a caller based on knowledge of a particular television program. The program may be broadcast at different times in different geographic areas, and as a consequence it may be desirable to limit calls inter-  
10 facing the processor format depending on the area code of calling numbers. Accordingly, time tests may involve solely the instant time, or various combinations of time and call data. The specific test is determined as indicated by a block 46 (FIGURE 2) imposing detailed operating instructions for the format. The test results  
15 are then correlated as represented by a block 48.

As indicated above, in accordance with the described embodiment, another test involves a record as for example directed to the station identified by the calling number. As an example, the record might take  
20 the form of either a negative or a positive file (for an individual format). In that regard, all formats involving "pay to dial" (e.g. 976, 900 etc.) calls might be conditioned as a group. Generally, in the case of a negative file, certain numbers are recorded that are to  
25 be denied access to a particular operating format. In the case of a positive file, access to the operating format is available only to calling numbers listed in the file.

Considering exemplary implementations of the  
30 system, a negative file may be based on limited or restricted use (as in the case of a lottery) or prohibitive use (telephone terminal owner choice). Formats accessible on a "one-time only" basis also may be controlled by negative lists. Thus, an operating format  
35 may be inaccessible to a terminal, or may be accessible



0048543-060795  
5 a specified number of times during a specified interval, e.g. three accesses per week. The historical test is symbolized in FIGURE 2 by the query block 50 to conditionally actuate the related tests as indicated in the block 48. History limitations also may involve purely format limits. For example, a give-away or dial-free format may be limited to some predetermined number of calls for a period, e.g. ten thousand calls per day. Thus, limits can be imposed on the economic exposure of a format.

10 Moving from the historic considerations, demographic tests may be specified as in relation to the geographic area manifest by the area code of the calling number. To consider a specific example, a public opinion poll may be conducted in which a particular geographic balance is defined. In such an operating format, calls may be accepted only until particular quotas are attained with respect to specified area codes. Such tests in the process are indicated by the query block 52, again to instruct the correlation block 48.

20 With the requisite tests established by selection of a format, the block 48 indicates resolving the acceptability of the call for the selected interface format. If the call is accepted, the process moves to initiate the selected format interface as indicated by the block 40. Conversely, if the call is to be rejected, the process moves to the step indicated by block 32, i.e. reject the call as with a message and release the line.

30 If a call is accepted, as represented by the block 40, there is a possibility that an established format may be aborted in favor of a different format. For example, interfacing the processor P, a qualified caller may fail to communicate digitally with the result

35

15

that transfer to a live operator is commanded. Also, in certain situations, a connection to a live operator is to be terminated in favor of an interface to the processor. In either event, an existing format is terminated in favor of a fresh format. That phase of the process is illustrated by an "abort" line from the block 40 returning to the block 28. Thus, the process returns to re-assign the caller to a new format in accordance with fresh data. Thus, transfers according to class 3 operation are implemented along with the other classes of operation by the switch SW (FIGURE 1).

An exemplary detailed structure of the switch SW (FIGURE 1) for executing the process of FIGURE 2 is represented in FIGURE 3. In that regard, individual telephone calls are manifest from the call receiver unit CU (FIGURE 1) comprising existing equipment as well known in the prior art. The call data is supplied through a line 60, upper left, FIGURE 3. Note that the represented single line 60 is merely symbolic of a channel to carry call data and provide direct telephone communication.

Generally, the system of FIGURE 3 illustrates elements of the switch SW of FIGURE 1 for processing an individual call. As indicated above, the system of the present invention involves the simultaneous processing of many calls with the possibility that numerous calls are simultaneously being tested for a connection as explained above. Consequently, although the system of FIGURE 3 is illustrated with respect to testing a single call, it is to be understood that sequential or parallel operations and multiplexing techniques, as well known and widely practiced in the computer field, are utilized to accomplish multiple processing operations as are described below with reference to FIGURE 3.

567099-TECHN

The line 60 (FIGURE 3, upper left) enters a line capture unit 62 through which signal-represented call data is supplied to a call data register 64. Accordingly, the call data is registered to be available for processing operations as explained generally with reference to FIGURE 2.

The line capture unit 62 also is connected to a control unit 66. Structurally, the control unit 66 may take the form of various computer facilities incorporating memory and logic capability to sequence and control specific functions as explained below. Generally, the control unit 66 implements specific formats which may involve coupling a caller either to a live operator station OS1-OSn or to the processor P. In that regard, the control unit 66 provides a series of timing signals t1-t6 to sequence the operations of individual component blocks as illustrated. Note that to preserve clarity in FIGURE 1, connections of timing signals t1-t6 are not illustrated. Also, the control unit 66 is connected to the operator stations OS1-OSn (line 67) to receive signals indicative of the availability of stations.

In addition to logic for controlled switching as described, the control unit 66 specifically includes a call register 68, a control register 70 and test control logic 72. The control register 70 receives format control words specified, as by the called number and having a form as illustrated in FIGURE 4.

Recapitulating, each of the operating formats has a control word for defining any access conditions or limitations to accomplish a specific format, e.g. connection to an operator station OS1-OSn or to the processor P (FIGURE 1). The formats may vary considerably; however, a few examples are the following:

5           Class 1, connect the live operator if available and provide prompt data for the XYS Company telemarketing program, if operator not available, cue caller: "All operators are busy at the moment, but we will return your call as soon as possible. Please touch your telephone buttons '2' and '4' to identify yourself as twenty-four for the return call".

10           Class 2, couple qualified callers to computer P for polling interface.

15           Class 3, couple callers to computer P for the RST Company telemarketing program, however, transfer to live operator (and prompt) if caller is not responsive.

20           These formats are established by control words that are selected on the basis of call data. The control words are sixteen bits, illustrated as the first sixteen bits (1-16) registered as shown in FIGURE 4. An additional group of registered bits (17-20) are provided from call data.

25           The initial three registered bits in the control register (FIGURE 4) serve as test command bits respectively for a time test, a history test and a demographics test. The presence of a "1" bit in any of the first three bit locations specifies the requirement for testing compliance to specified conditions. A "0" bit indicates no test.

30           The bits "4 through 7" in the control register constitute a field 74 and specify time conditions in relation to the instant time of the call. The field 74 may specify eight distinct time conditions. For exam-

ple, exemplary specified conditions for a format might be as follows:

5                   Accept calls between 7:00 and 18:00,  
                   Accept calls on Thursday between 9:00  
                   and 10:00,  
                   Accept calls from area code 213 on  
                   Wednesday between 15:00 and 16:00,  
 10                  Accept calls from area code 602 on  
                   Wednesday between 16:00 and 17:00.

Essentially, the time condition field 74  
 (activated by the time bit "1" - first bit position)  
 defines specific intervals during which calls will be  
 15               accepted for the specific called number and may be fur-  
                  ther limited by the area codes. A wide range of possi-  
                  bilities are available to accommodate specific programs  
                  for individual formats.

A field 76 in the control register embraces  
 20               bits "8" and "9" and defines the conditions for access  
                  to the format based on historical considerations. Thus,  
                  two bits are provided to indicate four possible histor-  
                  ical limitations. Again, the test is specified by a "1"  
                  bit, in this instance in the second bit location of the  
 25               register 70. The following limitations are exemplary of  
                  many possibilities as related to a single telephone  
                  number:

30                   Accept one call per day (per caller),  
                   Accept one call per week (per caller),  
                   Accept one call per month (per caller),  
                   Accept one call during any three-  
                   day period (per caller),  
                   Accept only 10,000 calls (per format).

35

Continuing with respect to the contents of the register 70, as illustrated in FIGURE 4, bits "10" and "11" constitute a field 78 specifying demographic test limitations. Again, a few examples will illustrate the various possibilities:

5                   Accept calls only from area code 213,  
                  Accept calls from area codes 213, 818  
                  and 619,  
10                  Accept only 1,000 calls from area  
                  code 213,  
                  Accept calls from area code 213 with  
                  the prefix numerals 619.

15                  Again, the demographic test is imposed only  
                  upon the existence of a "1" bit, in this instance in the  
                  third bit of the control word. As in the other cases,  
                  specific possibilities are considerable.

                  The bits "12" through "16" of the control word  
20                  constitute a field 80 and designate a selection code for  
                  the identified format. These five bits enable a sub-  
                  stantial number of formats to be designated and coded  
                  with respect to various classifications. For example,  
25                  calls of the class 1 specifying a desirable connection  
                  to a live operator station OS1-OSn might be encoded in a  
                  "000" decimal series, e.g. "001" indicates XYZ Company  
                  telemarketing program, "034" indicates RST Company  
                  program, and so on. Accordingly, a "0" in the most  
                  significant digit specifies a live operator format.  
30                  Similarly, lottery formats might be encoded in a "100"  
                  decimal series, e.g. "101, 102, 103 --- 110, 111, 112" -  
                  -- and so on; auctions might be designated in a "200"  
                  series, e.g.: "201, 202, --- ". By using decimal  
                  equivalent coding formats for various categories,  
35                  exclusions may be concisely stated. For example, a

calling number may be excluded from all lottery operating formats simply by the specification of decimal "100" in association with the calling number.

5 The data, as illustrated in FIGURE 4 is loaded into the control register 70. Again, the first sixteen bits comprise the format control word and are provided from a look-up table 84 (FIGURE 3, right, central) upon being addressed by call data from the register 64.

10 The last bits (bits 17-20) stored in the control register 70 are provided from an equipment and billing instruction index 86. That is, in response to the signal-represented call data indicating the called number and the equipment, the look-up table 84 and the index 86 supply data for loading the control register as  
15 indicated above.

While the control register 70 is loaded to specify the operation of the system, the call register 68 in the control unit 66 receives signals for additional control and to formulate a record of the call.  
20 Specifically, as represented in FIGURE 5, the contents of the call register 68 includes an initial validity bit 88 for indicating that the called <sup>in</sup>number is either on a positive list or is not on a negative list. The determination of the validity bit for location 88 is made by  
25 reference to a memory 90 (FIGURE 3, central) addressed by the calling number.

While the calling number addresses data to indicate a validity bit, specific format exclusions also may be indicated as explained above with respect to  
30 certain formats. For example, certain classifications of formats or specific formats (as a lottery) may be identified as inaccessible for certain telephone terminals as identified by calling numbers. Other than lottery formats, certain discretionary formats also may  
35 initiate control to limit access. Accordingly, a field

5640990-050730

21

89 in the call register 68 (FIGURE 5, bits "2" through "6") is provided from the memory 90, addressed by the calling number to specify format exclusions. That is, the calling number addresses the memory 90 to load the field 89 and specify limitations. Consider a few examples of format exclusions or limitations for a calling number:

No lottery formats,  
One lottery format per week,  
Two lottery formats per month of  
total cost under \$25.00,  
No auction sales,  
Auction sales only with caller  
entered code I.D. 763.

Again, it will be apparent that many possibilities exist in applying various coding techniques, the above merely being exemplary. Also, as indicated above, a format may be void of any limitations or restrictions. In that event, as explained above, a connection or interface is promptly commanded by the format code.

The bits "7" through "26" stored in the call register 68 (FIGURE 5) constitute a field 91 and indicate the time of a call. Signals representative of the instant time of a call to load the field 90 are provided from a time clock 92 (FIGURE 3, upper left). Signals from the time clock 92 may be in a Julian code and are provided to the call register 68 and also to a time test logic network 94 (lower left).

The last bits (27-30) in the register 68 are provided from the call data. The bits "27" and "28" indicate format billing data and comprise a field 82. Again, representations are coded; however, with respect to the field 82 information is derived from the called

0040543 060795

22



number. For example, an "800" called number may indicate no billing with the representative code being stored in the field 82. As another possibility, a "976" prefix number, or "900" number, may indicate a specific charge in relation to the identified format.

The bits "29" and "30" comprise a field 83 and may actuate a special form of the selected format. In the disclosed embodiment, the field 83 registers call data, as to indicate that the calling terminal is a "pulse" (rotary dial) signal unit or a "tone" (touch) signal unit. In the instance of a rotary terminal, the format program may be modified to accommodate "pulse" signal operation or inject operator communication with a transfer to one of the stations OS1-OSn.

Recapitulating to some extent with regard to the composition of the call record word in the register 68 (FIGURE 5), the memory 90 (FIGURE 3) is addressed by calling number data to provide data for the validity bit location 88 and the format-exclusion field 89. The time of call is stored in the field 91 from the clock 92. The billing and equipment data are provided by the index 86 in response to "calling" data signals.

Another element of memory, specifically, a recent activity storage 98 (FIGURE 3, lower right) is separately illustrated for convenience of explanation. Essentially, the storage 98 receives words from the call register 63 to maintain a record of interface calls. The recent activity storage may periodically be purged to permanent storage if desired. Thus, the recent activity storage 98 accumulates an activity record of all interface participants with respect to specific formats and is utilized in the history test for determining that an instant calling terminal is within the specified historical limitations as provided from the memory 90.

23

The activity tests are performed by a history test logic network 100 (FIGURE 3, lower central). In a related context, the demographics test as explained in detail above is performed by a demographics test logic network 102. The results of the test logic networks are communicated to the test logic 72 in the control unit 66. As a consequence, a switch unit 105 is actuated to either operatively couple the line 60 into a port of the processor P (FIGURE 1) or reject the call. If a call is accepted for an interface, a signal is supplied from the test control logic 72 through a line 107 to the switch 105 during the interval of the timing signal T6. The signal in the line 107 also is supplied to a format address register 109 for addressing the processor P. The register 109 stores select data signals to address a specific operating format of the processor P.

Recapitulating to some extent, call data indicates an interface format of the processor P (FIGURE 1) with associated limitations, conditions and billing provisions. Call data also indicates possible format limitations or conditions for a calling number. The system processes the data with respect to the conditions and limitations to selectively enable interface operations. Essentially, the call data specifies a format (processor or operator) and any conditions relating to the format. Representative data accordingly is provided from the look-up table 84 and the memory 90 to the control register 70 and the call register 68 respectively. Preliminary conditions may or may not be involved; however, qualified calls for an operator involve tests of availability within the control unit 66 according to data received from the stations OS1-OSn (line 67). As a result, calls are either interfaced to an operator who receives a format prompt, or interfaced to the processor according to a specified format.

24

[illegible]

15

20

30

35



the control unit 66. In that regard, a voice generator 106 (FIGURE 3, left central) may be actuated by the control unit 66 branching to the operation of timing signal t6. Accordingly, a message of denial may be provided on the line 60 prior to release of the line. Note that the voice generator 106 may be variously used to prompt or inform callers in certain preliminary selection operations supplemental to the specific operations disclosed below.

As indicated above, concurrently with the loading of the call register 68 (timing signal t2), the control register 70 also is loaded. Specifically, from the register 64, the called number cues the look-up table 84 to fill most of the control register (bits "1" through "16", FIGURE 4). The fields 82 and 83 are supplied from the index 86.

That is, distinct from the fields loaded into the control register 70 from the look-up table 84, the fields 82 and 83 are supplied from the index 86. In that regard, assume the called number (area code 976) indicates that the charge for the service of the call will be billed through the caller's telephone records. Assume that the field 83 indicates a "tone" terminal effective for a conventional digital interface.

At this point, some still further assumptions will be made to pursue the explanation of the detailed operations. Specifically, assume that the format specified by the called number ("900 513 7777") is a lottery format and includes limitations with respect to time, history and demographics. Accordingly, the initial three bits of the control word all will be "1" bits in the control register 70.

Assume further that the time conditions specified by the field 74 (FIGURE 4) limit calls from area code 415 to days other than Sunday. Assume that the

00435143-060795

history field 76 of the control word imposes a limitation of one call per day per calling station. Assume that the demographics field 78 excludes any call from area codes "512", "412", "812", --- (not "415").

5 Finally, assume the selected format (field 80) designates a specific lottery format, that is lottery "128".

In addition to registration of the data sets detailed above, because a history test is specified, the recent history storage 98 is cued during the interval of  
10 timing signal t3. The operation is through the memory 90 by the control unit 66 to prompt the supply of historical data (previously registered record words) for the telephone terminal designated by the calling number ("415 318 4444"). Specifically, during the interval of  
15 timing signal t3, the storage 98 supplies data on the calling number to the history test logic network 100. Such data is compiled into a test format as to indicate the number of calls per day, per week, and so on. Note that aggregate call totals may also be supplied as a  
20 test criteria. Thus, the control unit 66 coordinates the test criteria data preparatory to the test operations of the individual logic networks 94, 100 and 102.

To summarize, in accordance with the above assumptions, the test control logic 72 is set up to  
25 coordinate the following specific logic tests:

Time limitation test by network 94:  
accept calls from area code 415 except on  
Sunday,

30 History limit test by network 100:  
accept only one call per day per station,

Demographics test by network 102:  
accept no calls from area codes 512, 412,  
812 --- (415 not listed).

35

03495143 06095

27

As explained above, in addition to the limitations specified, in relation to the format, further limitations may be specified by the calling number. Such limitations are specified by the field 89 in the register 68 (FIGURES 3 and 5). In the instant example, assume that according to the record word, participation in the lottery format is limited to the interval between 10:00 a.m. and 3:00 p.m., e.g. when minors are in school. The code for such a format is supplied during the interval of timing signal t3 from the field 89 of the call register 68 to further establish the set-up of the logic 94 acting through the test control logic 72.

Recapitulating with regard to the test control logic 72, essentially a program is defined imposing each of the limitations that are specified by the call data in sufficient detail that comparison tests are expediently performed by the networks 94, 100 and 102. It is stressed, as indicated above, that the tests are selectively performed only in the event a "1" bit appears in the representative first three bit locations of the control word format. In the illustrative example, all the tests were commanded and accordingly the test control logic 72 sets up the condition for tests to be performed by the networks 94, 100 and 102, all during the interval of timing signal t3. Of course, the specific example represents one possibility of a substantial number of programs that might be specified to the system.

With the test formats established in the test control logic 72, the logic networks 94, 100 and 102 are driven during the interval of test signal t4 to execute a program in accordance with the assumed example. The process may be variously implemented in logic using well known techniques and is detailed in FIGURE 6. Consider the time test of the network 94. The time test logic

034451.06095  
562090 ETTS480

network 94 approves an interface only if: the call is not from area code "415" on a Sunday and furthermore the call occurs between the hours of 10:00 a.m. and 3:00 p.m. As indicated in FIGURE 6, a decision block 120  
 5 resolves the area-code "415" time test. If the area code is not "415", the logic proceeds to the next query block 122. Alternatively, if the area code is "415", the day must be tested against Sunday as indicated by the query block 124. An affirmative indication from the  
 10 Sunday test of block 124 prompts a rejection as indicated by the block 126.

If the Sunday test of block 124 is passed, the program imposes another time test, that is the time-of-day test as indicated by the block 122. Again, a  
 15 negative result prompts a rejection; however, a positive result involves the next step as indicated by the block 128.

Note that the operations designated by query blocks 120, 122 and 124 are performed by the time test  
 20 logic network 94 (FIGURE 3). The next test of the block 128 is performed by the history test logic 100. The block 128 (FIGURE 6) involves a determination of whether or not the instant call is the first for the calling terminal on the instant calendar day. If not, the  
 25 limitations are exceeded and the call is rejected. If the test is passed, the process next involves the demographic test logic network 102 (FIGURE 3) to determine whether or not the call originated from an excluded area based on the calling number area code.

Area controls are illustrated by the query  
 30 block 130 of FIGURE 6. Specifically, the demographics test logic network 102 determines whether or not the current call is from a denied area. If so, the call is rejected as indicated by the block 126. Alternatively,  
 35 if the area is not excluded, as illustrated by the block

004544 060793  
 004544 060793

134 in FIGURE 6, the interface is accepted. In the instant case, the area "415" is acceptable.

In the operation of the system as illustrated in FIGURE 3, the logic networks 94, 100 and 102 indicate test results to the test control logic 72 during the interval of the timing signal t5. The logic 72 correlates the test result for action by the control unit 66. If the imposed conditions are met (or if there are no conditions) the control unit 66 actuates the switch unit 105 and the address register 109 through the line 107 to perfect the interface from the line 60 (upper left) to either a port in the processor P (FIGURE 1) or one of the operator stations OS1-OSn. Essentially, the switching operation occurs during the interval of the timing signal t6. Concurrently, the address register 109 specifies the select operating format as stored in the processor P for direct use in an interface with a caller, or to be retrieved and supplied through the switch SW to prompt an operator at a station OS1-OSn.

Also during the interval of the timing signal t6, the contents of the call register 68 is stored in the recent history storage 98. Note that billing data is stored with the call words and may be selectively extracted from the storage 98. At the termination of the timing signal t6, the interface endures until there is a "disconnect" or an "abort".

If the processor P senses the existence of conditions specifying a shift between a processor interface and a live operator communication, the control unit 66 is actuated as indicated through line 115. Note that the abort signal is formed either in response to predetermined conditions in an interface with the processor P, or on command from an active operator station. The signal is also supplied to the look-up table 84 which becomes active if a transfer is condi-



tional. That is, if a transfer is conditional, the tests as described above may be invoked. Conversely, if the transfer is unconditional, the control unit 66 simply actuates the switch 105 to make the change and prompts the format address register to establish the desired format or prompt pattern for an operator.

The formats may involve various records, however, in accordance with the system of the present invention affords considerable flexibility to program individual conditions and limitations for each interface format based on the call data (calling number and called number). An interface may involve no conditions or conditions may be imposed from the called number (format selection), the calling number, or both.

Accordingly, effective control may be imposed depending upon the service requested as manifest by an individual format, the instant time, the history of use and the demographics involved. The imposed limitations may be non-existent or may involve a relatively complex test pattern as explained in detail above.

In the disclosed embodiment, an effective record of calls is accumulated in the recent history storage 98. Thus, a composite and detailed record is accumulated of individual calls as executed.

It is to be appreciated that numerous formats may be implemented and controlled utilizing the principles of the system as illustrated above. Accordingly, it is to be understood that the system of the present invention should be interpreted in accordance with the claims as set forth below.

554,090" E.T. 5-8-48

## WHAT IS CLAIMED IS:

- 1                   1. An interface control system for use with,  
2                   (1) a communication facility including remote terminals  
3                   for individual callers, wherein said remote terminals  
4                   may comprise a conventional telephone instrument includ-  
5                   ing voice communication means and digital input means  
6                   for providing data, (2) a multiple port, multiple format  
7                   processor for interfacing a substantial number of  
8                   callers in any of a plurality of formats to concur-  
9                   rently process data, and (3) a plurality of live opera-  
10                  tor stations with prompting capability, for a plurality  
11                  of formats, said interface control system comprising:  
12                  call data means for receiving signal-  
13                  represented call data from said terminals;  
14                  selection means for selecting one of said  
15                  formats under control of said call data means to thereby  
16                  further specify any defined conditions for a connection  
17                  of a call either to said multiple port, multiple format  
18                  processor or one of said live operator stations, at  
19                  least one of said formats having at least one specified  
20                  condition; and  
21                  interconnect switch means for providing format  
22                  data and controlling connections from a calling remote  
23                  terminal to a port of said multiple port, multiple  
24                  format processor or one of said live operator stations  
25                  under control of said selection means.

- 1                   2. A system according to claim 1 further  
2                   including test means to specify test conditions for  
3                   certain of said formats and means to test compliance  
4                   with said conditions to further control said intercon-  
5                   nect switch means.

0043511 060745

1           3. A system according to claim 2 wherein one  
2 of said test means comprises means for executing a test  
3 based on the time of a call.

1           4. A system according to claim 2 wherein one  
2 of said test means comprises means for executing a test  
3 based on the history of the calling remote terminal.

1           5. A system according to claim 2 wherein one  
2 of said test means comprises means for executing a test  
3 based on the demographics of the calling remote terminal.  
4

1           6. A system according to claim 1 wherein said  
2 selection means includes a look-up table for specifying  
3 said formats addressed by call data.

1           7. A system according to claim 1 wherein said  
2 selection means includes a control storage location and  
3 means for setting control data in said control storage  
4 location responsive to said call data.

1           8. A system according to claim 1 further  
2 including a voice generator means for prompting a  
3 caller.

1           9. A system according to claim 1 further  
2 including means for storing data representative of  
3 calls.

1           10. A system according to claim 9 wherein  
2 said means for storing includes means for storing  
3 billing data.

0944543 060795  
562099 074430

1 11. A system according to claim 1 further  
2 including means to provide an abort signal, the system  
3 being responsive to said abort signal to reactuate said  
4 interconnect switch means for providing alternative  
5 connections with format data.

1 12. A system according to claim 11 further  
2 including test means to specify test conditions for  
3 certain of said formats and means to test compliance  
4 with said conditions to further control said intercon-  
5 nect switch means.

1 13. A system according to claim 1 wherein  
2 said selection means selects under control of DNIS  
3 signals.

1 14. A system according to claim 1 wherein  
2 said selection means selects under control of ANI  
3 signals.

1 15. A system according to claim 1 wherein  
2 said selection means selects under control of equipment  
3 type signals.

1 16. An interface control system for use with,  
2 (1) a communication facility including remote terminals  
3 for individual callers, wherein said remote terminals  
4 may comprise a conventional telephone instrument includ-  
5 ing voice communication means and digital input means  
6 for providing data, (2) a multiple port, multiple format  
7 processor for interfacing a substantial number of  
8 callers in any of a plurality of formats to concur-  
9 rently process data, and (3) a plurality of live opera-  
10 tor stations with prompting capability, for a plurality  
11 of formats, said interface control system comprising:

5044306430

12 call data means for receiving signal-  
13 represented call data from said terminals;

14 selection means for selecting one of said  
15 formats under control of said call data means to thereby  
16 further specify any defined conditions for a connection  
17 of a call either to said multiple port, multiple format  
18 processor or one of said live operator stations, at  
19 least one of said formats having at least one specified  
20 condition;

21 test means for testing the specified condi-  
22 tions to provide approval signals; and

23 interconnect switch means for providing  
24 connections from a calling remote terminal to a port of  
25 said multiple port, multiple format processor or one of  
26 said live operator stations under control of said  
27 selection means and conditional, in conditioned formats,  
28 on an approval signal from said test means under control  
29 of said approval signals from said test means.

1 17. A process for interfacing a telephonic  
2 communication system including remote terminals either  
3 with a multiple port, multiple format data processing  
4 system, said multiple port, multiple format data proces-  
5 sing system for concurrently processing data from said  
6 remote terminals according to a plurality of formats, at  
7 least one of said formats having at least one condition  
8 for a calling terminal, or one of a plurality of opera-  
9 tor stations with prompting capability for a plurality  
10 of formats, and wherein said telephonic communication  
11 system provides call data signals, as to indicate called  
12 and calling numbers, said process including the steps  
13 of:

14 receiving said call data signals from said  
15 telephonic communication system for a calling remote  
16 terminal;

0044343 000095

add  
G7

DECLARATION AND PETITION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled MULTIPLE FORMAT TELEPHONIC INTERFACE CONTROL SYSTEM, the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed: None.

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37,

00405443 060795

Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

260,104	October 20, 1988	Pending
Application Serial No.	Filing Date	Status
4,792,968	December 20, 1988	
Patent No.	Issued	
753,299	July 10, 1985	Abandoned
Application Serial No.	Filing Date	Status

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Wherefore I pray that Letters Patent be granted to me for the invention or discovery described and claimed in the foregoing specification and claims, and I hereby subscribe my name to the foregoing specification and claims, declaration and petition.

1-00 Full name of sole or first inventor: Ronald A. Katz

Inventor's signature: [Signature]

Date: 4/3/90

Residence: Los Angeles, California

Citizenship: U.S.A.

Post Office Address: 570 South Mapleton Drive  
Los Angeles, California 90024

CA



POWER OF ATTORNEY BY ASSIGNEE

Commissioner of Patents  
and Trademarks  
Washington, D. C. 20231

Sir:

I, Aldo Tesi, Executive Vice President of FIRST DATA RESOURCES INC., a corporation of the State of Delaware and assignee of the entire right, title and interest in the application for United States Letters Patent entitled MULTIPLE FORMAT TELEPHONIC INTERFACE CONTROL SYSTEM and executed on April 3, 1990, with inventor Ronald A. Katz, hereby appoint:

<u>Attorney</u>	<u>Registration No.</u>
Byard G. Nilsson	17,350
Billy A. Robbins	18,313
Lewis M. Dalgarn	20,415
Robert Berliner	20,121
M. John Carson	25,090
Harold E. Wurst	22,183
Michael S. Elkind	28,710
Gregory B. Wood	28,133
Robert A. Green	28,301
Mark E. Garscia	31,953
John P. Spitals	29,215
Jeffrey F. Craft	30,044
Georgann S. Grunebach	33,179

all attorneys of the law firm of Nilsson, Robbins, Dalgarn, Berliner, Carson & Wurst, Fifth Floor, 201 North Figueroa Street, Los Angeles, California 90012-2628, as attorneys of said corporation with full powers of substitution and revocation to prosecute this application and to transact all business in the United States Patent and Trademark Office in connection therewith.

Please send all correspondence to:

B. G. Nilsson  
NILSSON, ROBBINS, DALGARN,  
BERLINER, CARSON & WURST  
201 North Figueroa Street, Fifth Floor  
Los Angeles, California 90012-2628  
U.S.A.

Telephone (213) 977-1001

FIRST DATA RESOURCES INC.

By:

*Aldo Tesi*

Aldo Tesi

Executive Vice President

Attorney Docket No. 4646-108C

0046543 06093E  
564090 CT59190



PATENTS

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Ronald A. Katz )  
Serial No.: 08/306,751 ) Examiner in parent  
Filed: September 14, 1994 ) case: S. Woo  
For: MULTIPLE FORMAT TELEPHONIC ) Art Unit: 2608  
INTERFACE CONTROL SYSTEM )  
New Docket No.: 6646-108N3 )  
(Previous Docket No.: 4646-108N3) )

POWER OF ATTORNEY BY ASSIGNEE

Commissioner of Patents  
and Trademarks  
Washington, D. C. 20231

Sir:

I, Ronald A. Katz, am the President of A2D Corporation, a California corporation, which corporation is a general partner of A2D, L.P., a California limited partnership, which limited partnership is a general partner of RONALD A. KATZ TECHNOLOGY LICENSING, L.P., a California limited partnership and assignee of the entire right, title and interest in the application for United States Letters Patent entitled MULTIPLE FORMAT TELEPHONIC INTERFACE CONTROL SYSTEM, and am authorized to sign on its behalf.

The Assignment of this application to RONALD A. KATZ TECHNOLOGY LICENSING, L.P., has been submitted to the Assignment Branch and was received on September 26, 1994.

I have reviewed the foregoing document and hereby certify that, to the best of my knowledge and belief, title to the

subject matter of this patent application is in RONALD A. KATZ  
TECHNOLOGY LICENSING, L.P.

I hereby appoint: Byard G. Nilsson, Reg. No. 17,350, Harold  
E. Wurst, Reg. No. 22,183, Robert A. Green, Reg. No. 28,301, Anne  
Wang, Reg. No. 36,045, all members of the bar of one or more  
states, Reena Kuyper, Patent Agent, Reg. No. 33,830, all of the  
law firm of Nilsson, Wurst & Green, 707 Wilshire Blvd., 32nd  
Floor, Los Angeles, California 90017; and Thomas J. Lannon,  
Registration No. 18,417, 105 Whittier St., NW, Washington, DC  
20012, to prosecute this application and to transact all business  
in the United States Patent and Trademark Office in connection  
therewith.

Please send all correspondence to:

NILSSON, WURST & GREEN  
707 Wilshire Blvd., 32nd Floor  
Los Angeles, California 90017  
U.S.A.


Telephone (213) 243-8000

RONALD A. KATZ TECHNOLOGY  
LICENSING, L.P., a California limited  
partnership,

By: A2D, L.P., a California limited  
partnership, its general partner

By: A2D Corporation, a California  
corporation, its general partner

By:

  
Ronald A. Katz  
President,  
A2D Corporation

Attorney Docket No. 6646-108N3

6646\108N3 poa

1011  
mi

A S S I G N M E N T

WHEREAS, I, RONALD A. KATZ, residing at 570 South Mapleton Drive, Los Angeles, California 90024, have invented a new and useful MULTIPLE FORMAT TELEPHONIC INTERFACE CONTROL SYSTEM for which I have this day executed application papers for United States Letters Patent thereon, said application being identified as Docket No. 4646-108C of the law firm of Nilsson, Robbins, Dalgarn, Berliner, Carson & Wurst; and


WHEREAS, FIRST DATA RESOURCES INC., a Delaware corporation, having its principal place of business at 10825 Farnum Drive, Omaha, Nebraska 68154, is desirous of acquiring the entire and exclusive right, title and interest in and to the said invention in the United States and throughout the world, and in and to any Letters Patent which may be granted and issued therefor;

NOW, THEREFORE, for the sum of One Dollar (\$1.00) and other good and valuable consideration, the receipt and sufficiency of which are hereby acknowledged, I the said RONALD A. KATZ, by these presents do hereby sell, assign, transfer and set over unto the said FIRST DATA RESOURCES INC., its successors and assigns, the entire and exclusive right, title and interest in and to said invention, in the United States and throughout the world, and in and to any Letters Patent which may be granted and issued therefor, and in and to any continuations, divisions, reissues and extensions of said Letters Patent and all interna-

REC-5282 PAGE 914

tional priority rights associated therewith; and I further agree to sign all papers and perform all acts, without any further consideration but at no cost or expense to me, as said FIRST DATA RESOURCES INC. may deem necessary to make this Assignment fully effective, including the execution of any and all original, reissue, divisional and continuing United States and foreign patent applications.

And, I hereby authorize and request the Commissioner of Patents and Trademarks to issue the said United States Letters Patent to said FIRST DATA RESOURCES INC., its successors and assigns.

  
\_\_\_\_\_  
Ronald A. Katz

STATE OF CALIFORNIA )  
COUNTY OF LOS ANGELES ) ss


On this 3rd day of April, 1990, before me, a Notary Public, personally appeared RONALD A. KATZ, personally known to me (or proved to me on the basis of satisfactory evidence) to be the person whose name is subscribed to the within instrument, and acknowledged to me that he executed the same.

IN WITNESS WHEREOF, I have hereunto set my hand and affixed my official seal the day and year first above written.

RECORDED  
PATENT AND TRADEMARK  
OFFICE

APR 16 1990

  
\_\_\_\_\_  
Notary Public



REC-5282 FRAME 915